

Data sheet LED pendent luminaire PSLG123

- Light up with: SMD LED
- System power: 44W / 57W
- Colour rendering index: CRI >80
- Power supply: with power supply
- Connection voltage: AC 230 V
- Energy efficiency: A++ - A
- Protection class: 1
- Test certificates: CE
- Material: extruded aluminium
- Colours: white, black, anodized aluminium



Technical data for PSLG123 44W

Colour temperature	2700K	3000K	4000K
Art.No. white	PSLG123-1200SW10	PSLG123-1200WW10	PSLG123-1200NW10
Art.No. black	PSLG123-1200SW20	PSLG123-1200WW20	PSLG123-1200NW20
Art.No. anodized aluminium	PSLG123-1200SW70	PSLG123-1200WW70	PSLG123-1200NW70
System power	44W		
Luminous flux	3924 lm	3924 lm	4307 lm
System efficiency	89 lm/W	89 lm/W	98 lm/W
Version: Light distribution	direct 67% / indirect 33%		
Dimensions L x B x H	1230 x 45 x 123 mm		

Technical data for PSLG123 57W

Colour temperature	2700K	3000K	4000K
Art.No. white	PSLG123-1500SW10	PSLG123-1500WW10	PSLG123-1500NW10
Art.No. black	PSLG123-1500SW20	PSLG123-1500WW20	PSLG123-1500NW20
Art.No. anodized aluminium	PSLG123-1500SW70	PSLG123-1500WW70	PSLG123-1500NW70
System power	57W		
Luminous flux	5084 lm	5084 lm	5538 lm
System efficiency	89 lm/W	89 lm/W	98 lm/W
Version: Light distribution	direct 67% / indirect 33%		
Dimensions L x B x H	1530 x 45 x 123 mm		