

REWARDING BRIGHTNESS



Accessories

Power supply units MLMC

Specifications

Material	PA
Frequency	50/60 Hz
Environment	Indoor
IP rate	IP20
Operating temperature	-20°C / +45°C
Safety marks	EN61347-1 / EN61547 / EN61547-2-13
EMC compliance	EN55015 / EN61000-3-2 / DIN VDE 0710-T14
Single carton quantity	1 pc
Package type	Plastic Bag
Warranty	7 Years

IP20

REWARDING BRIGHTNESS

Item specifications (part A)

Description	Item code	Watt	Stroom	Type
PSU 05CB 20W 700mA Triac	05CB03MLMC00	20W (28V)	350/500/700mA	Triac
PSU 05CD 20W 700mA Dali	05CD03MLMC00	20W (28V)	350/500/700mA	DALI
PSU 05CC 20W 700mA 1-10V & Push	05CC03MLMC00	20W (36V)	350/500/700mA	1-10V & Push
PSU 05CW 20W 700mA no-dim	05CW03MLMC00	20W (36V)	350/500/700mA	No-dim
PSU 05CV 26W 700mA no-dim	05CV03MLMC00	26W (37V)	350/500/700mA	No-dim
PSU 05CF 32W 700mA no-dim & ripple<20%	05CF03MLMC00	32W (32V)	700/900/1000mA	No-dim
PSU 05CG 32W 700mA Triac & Push	05CG03MLMC00	32W (46V)	350/500/700/900mA	Triac & Push
PSU 05CH 32W 700mA 1-10V & Push	05CH03MLMC00	32W (46V)	350/500/700/900mA	1-10V & Push
PSU 05CJ 32W 700mA Dali	05CJ03MLMC00	32W (46V)	350/500/700/900mA	DALI
PSU 05CT 39W 1050mA 1-10V	05CT03MLMC00	39W (37V)	700/900/1050mA	1-10V
PSU 05CZ 40W 1050mA Dali	05CZ03MLMC00	40W (38V)	700/900/1050mA	DALI
PSU 05BZ 42W 700mA no-dim	05BZ03MLMC00	42W (40V)	350/500/700mA	No-dim
PSU 05CY 42W 1050mA no-dim	05CY03MLMC00	42W (40V)	700/900/1050mA	No-dim
PSU 05CK 50W 1050mA no-dim	05CK03MLMC00	50W (48V)	700/900/1050mA	No-dim
PSU 05CL 50W 1050mA no-dim & ripple<20%	05CL03MLMC00	50W (48V)	700/900/1050mA	No-dim
PSU 05CM 50W 1050mA Dali & 1-10V & Push	05CM03MLMC00	50W (48V)	700/900/1050mA	DALI & 1-10V & Push
PSU 05CP 55W 1400mA no-dim	05CP03MLMC00	55W (39V)	1200/1400mA	No-dim
PSU 05CQ 55W 1400mA 1-10V & Dali & Push	05CQ03MLMC00	55W (39V)	1200/1400mA	DALI & 1-10V & Push

(part B)

Description	Efficiency	Pf	Ripple	Input Voltage	Dimensions	Weight	Inrush current	B-16A Fuse
PSU 05CB 20W 700mA Triac	89%	0.97	<20%	220-240V	110x52x22 mm	108 gr	2A 50µS	50 pcs
PSU 05CD 20W 700mA Dali	87%	0.92	<3%	220-240V	103x67x21 mm	115 gr	5A 50µS	50 pcs
PSU 05CC 20W 700mA 1-10V & Push	87%	0.95	<3%	220-240V	110x52x22 mm	112 gr	5A 50µS	50 pcs
PSU 05CW 20W 700mA no-dim	87%	0.93	<3%	220-240V	110x52x22 mm	108 gr	5A 50µS	50 pcs
PSU 05CV 26W 700mA no-dim	89%	0.95	<20%	220-240V	130x42x30 mm	109 gr	5A 50µS	50 pcs
PSU 05CF 32W 700mA no-dim & ripple<20%	89%	0.95	<20%	220-240V	166x46x34 mm	109 gr	5A 50µS	50 pcs
PSU 05CG 32W 700mA Triac & Push	85%	0.97	<3%	220-240V	103x67x21 mm	166 gr	5A 50µS	50 pcs
PSU 05CH 32W 700mA 1-10V & Push	88%	0.98	<3%	220-240V	103x67x21 mm	138 gr	5A 50µS	50 pcs
PSU 05CJ 32W 700mA Dali	87%	0.98	<3%	220-240V	103x67x21 mm	138 gr	5A 50µS	50 pcs
PSU 05CT 39W 1050mA 1-10V	90%	0.95	<3%	220-240V	103x67x21 mm	138 gr	5A 50µS	50 pcs
PSU 05CZ 40W 1050mA Dali	89%	0.95	<3%	220-240V	124x79x22 mm	150 gr	20A 400µS	50 pcs
PSU 05BZ 42W 700mA no-dim	90%	0.95	<3%	220-240V	130x42x30 mm	132 gr	5A 50µS	50 pcs
PSU 05CY 42W 1050mA no-dim	90%	0.95	<3%	220-240V	130x42x30 mm	132 gr	5A 50µS	50 pcs
PSU 05CK 50W 1050mA no-dim	89%	0.95	<3%	220-240V	129x76x30 mm	208 gr	20A 400µS	50 pcs
PSU 05CL 50W 1050mA no-dim & ripple<20%	90%	0.95	<20%	220-240V	160x83x35 mm	184 gr	5A 50µS	50 pcs
PSU 05CM 50W 1050mA Dali & 1-10V & Push	89%	0.95	<3%	220-240V	124x79x22 mm	218 gr	20A 400µS	50 pcs
PSU 05CP 55W 1400mA no-dim	90%	0.98	<3%	220-240V	173x83x35 mm	284 gr	10A 200µS	20 pcs
PSU 05CQ 55W 1400mA 1-10V & Dali & Push	89%	0.98	<3%	220-240V	173x83x35 mm	284 gr	10A 200µS	20 pcs

The power supply units will be delivered including yellow TE plug at the secondary side.

