

## Data sheet LED pendent luminaire PSL

- Light up with: SMD LED
- System power: 44W / 57W
- Colour rendering index: CRI >80
- Power supply: included
- Operation voltage: 230 VAC
- Energy efficiency: A++ - A
- Protection class: 1
- Test mark: CE
- Material: extruded aluminium
- Colours: white, black, anodized aluminium



### Technical data for PSL100 44W

Colour temperature	2700K	3000K	4000K
Art.No. white	PSL100-1200SW10	PSL100-1200WW10	PSL100-1200NW10
Art.No. black	PSL100-1200WW20	PSL100-1200WW20	PSL100-1200NW2
Art.No. anodized aluminium	PSL100-1200SW70	PSL100-1200WW70	PSL100-1200NW70
System power	<b>44W</b>		
Luminous flux	3544 lm	3544 lm	3890 lm
System efficiency	81 lm/W	81 lm/W	88 lm/W
Version: Light distribution	direct 68% / indirect 32%		
Dimensions L x B x H	1230 x 45 x 100 mm		

### Technical data for pendent luminaire PSL100 57W

Colour temperature	2700K	3000K	4000K
Art.No. white	PSL100-1500SW10	PSL100-1500WW10	PSL100-1500NW10
Art.No. black	PSL100-1500WW20	PSL100-1500WW20	PSL100-1500NW20
Art.No. anodized aluminium	PSL100-1500SW70	PSL100-1500WW70	PSL100-1500NW70
System power	<b>57W</b>		
Luminous flux	4592 lm	4592 lm	5002 lm
System efficiency	81 lm/W	81 lm/W	88 lm/W
Version: Light distribution	direct 68% / indirect 32%		
Dimensions L x B x H	<b>1530</b> x 45 x 100 mm		