

Zigbee Blinds Actuator Mini

Item number 57008000



Blinds actuator for control of electrical blinds, shutters or awning in a Zigbee 3.0 system. The device provides two inputs for connecting blind switches or -push-buttons. The installation takes place in the appliance box behind the switch/push-button or in the shutter housing next to the motor. Configuration and immediate function test via the Prog. button.

Product features

- › Zigbee Actuator to integrate with all Zigbee systems with Zigbee 3.0 Standard
- › Parameterisation via NEXENTRO config App
- › Updateable via NEXENTRO config App
- › 2 inputs for blinds or roller shutter control keys
- › 2 outputs for the control of electric blinds and shutters
- › Installation in appliance boxes behind blind or roller shutter control keys
- › Screw terminal for the through-wiring of existing conductors (max. 16 A)
- › Button and LED for commissioning and functionality tests



Technical data

Mains voltage	AC 230 / 240 V ~
Mains frequency	50 / 60 Hz
Connected load Motors	700 W
Standby Power consumption	max. 0.2 W
Running time	1 ... 120 s
Cable length Inputs	max. 3 m
Ambient temperature	-5 ... +45 °C
Storage/ transport temperature	-25 ... +70 °C
Dimensions (LxWxH)	approx. 48 x 51 x 20 mm

Zigbee	
Communication protocol	Zigbee 3.0 (Router)
Radio frequency	2.400 ... 2.483 GHz
Transmission capacity	1 mW

Bluetooth	
Radio frequency	2.400 ... 2.480 GHz
Transmission capacity	max. 2 mW, Class 2
Transmitting range	typ. 10 m