

REWARDING BRIGHTNESS




Sensor

LM SensorTune 50

LV 600 Lm tunable

Specifications

Colour	Matt black
Beam angle options	24° / 60°
Input voltage	24Vdc SELV (20-28Vdc)
Lumen output	600 Lm
Fixture material	Die cast aluminium
Environment	Indoor
IP rate	IP20
IK rate	IK03
Dimmable	Step
Operating temperature	-20°C / +45°C
Safety marks	EN60598 / EN62031 / EN62471
EMC compliance	EN55015
Colour consistency (SDCM)	MacAdam step 3
Warranty	7 Years




This luminaire contains built-in LED lamps

The lamps cannot be changed in the luminaire.



874/2012



Sensor luminaires turn on for 4 minutes after detecting movement. A different time can be set for large orders.

REWARDING BRIGHTNESS

Item specifications (part A)


Description	Item code	Type	Input	W	Lm	Lm/W	CRI (typ.)	UGR	Pf	Ripple	Inrush current	B-16A Fuse
LM SensorTune 50 LV 24° 3000K	100203BL8214	Incl. PSU	220-240V	8	600	75	83	19.9	0.6	<3%	20A 170µS	50
LM SensorTune 50 LV 24° 4000K	100203BL8914	Incl. PSU	220-240V	8	600	75	83	25.2	0.6	<3%	20A 170µS	50
LM SensorTune 50 LV 60° 3000K	100203BL9114	Incl. PSU	220-240V	8	600	75	83	19.9	0.6	<3%	20A 170µS	50
LM SensorTune 50 LV 60° 4000K	100203BL9214	Incl. PSU	220-240V	8	600	75	83	25.2	0.6	<3%	20A 170µS	50

Item specifications (part B)

Description	Safety class	Energy class	Weight	Dimensions single carton	Quantity per carton	Expected lifespan (25°C)		
						L70B50	L80B50	L90B50
LM SensorTune 50 LV 24° 3000K	II	A	264 gr	105x105x105 mm	45 pcs	282.168 hrs	178.352 hrs	87.206 hrs
LM SensorTune 50 LV 24° 4000K	II	A	264 gr	105x105x105 mm	45 pcs	282.168 hrs	178.352 hrs	87.206 hrs
LM SensorTune 50 LV 60° 3000K	II	A	264 gr	105x105x105 mm	45 pcs	282.168 hrs	178.352 hrs	87.206 hrs
LM SensorTune 50 LV 60° 4000K	II	A	264 gr	105x105x105 mm	45 pcs	282.168 hrs	178.352 hrs	87.206 hrs

All values are measured at 230V (+/- 7%).

Dimensions



Detection area

